



Il modello **WRM20+** permette di collegare il display **WRD** per il controllo remoto.

La **Western CO.** fornisce il protocollo di comunicazione su questa porta e quindi l'utente può implementare un proprio dispositivo datalogger o controllo remoto.

remote control.

rant de charge par le module PV, le courant de la charge branché en sortie et d'autres variables.

Le modèle **WRM20+** permet de connecter l'écran **WRD** pour le contrôle à distance. La société **Western CO.** fournit le protocole de communication sur ce port et l'utilisateur peut donc mettre en œuvre un propre enregistreur de données ou son dispositif de contrôle à distance.

Caratteristiche prodotto



Step down MPPT technology



For sealed/GEL, flooded lead acid batteries and lithium-ion batteries



18 programs for load management



IP20 metal box

[eng]

Product features



Max PV module power:
310W for 12V battery
620W for 24V battery



Temperature-compensated
charge voltage



LCD display user interface



WRD SYSTEM MONITOR ready,
(available only with WRM20+ version)

[fra]

Caractéristiques du produit



Integrated blocking diode



12V/24V battery auto-detect
voltage



Protections:
Low voltage load disconnect
Over-temperature
Battery polarity inversion
Output overload protection



WBUS protocol with RS485
communication port
(available only in WRM20+ version)



USER MANUAL
WRM20/20+

